



Knauf Soundshield Plus

Knauf Soundshield Plus is the ideal plasterboard where sound reduction is of particular importance. Its high mass gives an enhanced acoustic performance, excellent fire resistance and severe duty impact rating when used on Knauf systems.

Soundshield Plus is made from an aerated gypsum core, with premium paper liners on either side. Can be finished with Knauf Jointing Products and Knauf Ready mix spray finish before decoration.

Product-Data-Sheet

Areas of Application

Suitable for partitions, linings and ceilings where enhanced levels of sound performance are required. The 15mm board also offers increased impact and fire resistance over the 12.5mm variant.

Soundshield Plus is not suitable for high humidity areas.

Compliance Standards

12.5mm – EN520 A & D

15mm – EN520 A, D, F and I

Key Benefits

- Strong and versatile
- Enhanced levels of sound performance
- Tapered edge
- Fully recyclable
- Quick and easy to install
- Multiple layers can be used for added performance
- Provides a smooth surface ready for finishing

Build on us.

Creation Date: 11/08/2023
Revision Reference: 004
Revision Date: 31/03/2025

Performance Data

Thickness (mm)	Reaction to Fire (R2F)	Thermal Conductivity (λ) (W/mK)	Water Vapour Resistance (μ) (Dry/Wet) (EN12524)	Board Density (kg/m ³)
12.5	A2-s1, dO (B)	0.25	10/4	920
15	A2-s 1, dO (B)	0.25	10/4	887

Technical Information**Tapered Edge**

Thickness (mm)	Width (mm)	Length (mm)	Colour	Weight (kg/m ²)	Taper Width (mm) (Max/Min)	Taper Depth (mm) (Max/Min)	Number of Tapered Edges	Material Number
12.5	1200	2400	Blue	11.5	80/40	2.5/0.6	2	292622
		2700	Blue	11.5	80/40	2.5/0.6	2	292620
		3000	Blue	11.5	80/40	2.5/0.6	2	292627
15	1200	2400	Blue	13.3	80/40	2.5/0.6	2	292646
		2700	Blue	13.3	80/40	2.5/0.6	2	292677
		3000	Blue	13.3	80/40	2.5/0.6	2	292678

Sustainability

Recycled Content

12.64%

2024 average by mass for all UK produced plasterboards, recycled gypsum & paper

Recyclability

This product should be recycled separately to non-plasterboard waste. Please ensure it has no or minimal contamination from non-gypsum based materials, as this will affect its recyclability.

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Storage and Handling

Product must be stored flat and on a surface strong enough to support them. Keep boards dry at all times.

Refer to the HSE Manual Handling Operations Regulation for best practice guidance.

Packaging

Product is stacked on recycled chipboard bearers and can be recycled with wood waste.

Pallet wrap is made from 30% recycled plastic content.

Service Life

Service life of this product is 60 years and/or the lifetime of the building.

Disposal

Disposal should be in accordance with local authority requirements. Keep gypsum based products in their own recycling area to minimise contamination from non-gypsum based products. European Waste Catalogue code: 17 08 02

Health & Safety

Please refer to our Safety Data Sheet for guidance on Personal Protection Equipment required for the handling and installation of this product.

Application / Installation

Typically installed as a part of a partition system, wall lining and ceiling system with Knauf fixings, jointing, taping and finishing products.

Use Knauf plasterboard screws at a distance of 300mm on horizontal joints and 10mm from bound edge and 13mm from unbound edges in from the edge of the board.

Knauf Jointing Compounds with Knauf Paper Joint Tape can be used to finish the joints followed by Knauf Wallboard Primer prior to decoration. Knauf Ready Mix Airless Finishes (RMF), can be spray applied to the board following the jointing process. No Wallboard Primer would be required if using RMF to finish. It can also be direct bonded.

Should an alternative Gypsum or surface finish be required, seek guidance from the supplier on application.

The type and number of layers of board used will influence the structural, fire, acoustic and thermal performance of the system.

All products must be installed in accordance with Knauf's recommendations and the current recommendations of BS 8000-8 2023.

Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

Certification

[Environmental Product Declaration](#)

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

Tel: 0800 521050 (option 2)
Email: technical-uk@knauf.com
(excluding public holidays)

UK Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Ireland Address

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

Creation Date: 11/08/2023
Revision Reference: 004
Revision Date: 31/03/2025