

PRELUDE XL32

24mm (15/16") Exposed Tee System

BENEFITS

- Hot dipped galvanized coating inhibits red rusting better than electrogalvanized, painted or plated systems.
- Rotary stitched for additional torsional strength and extra stability during installation.
- Tighter tee to tee connection of XL cross tee.
- Easy to remove and relocate.
- System is engineered and designed to coordinate with Armstrong & Thermatex Ceilings.

Material

Double-web hot dipped galvanized steel

Surface Finish

Baked polyester paint

Cross Tee/ Main Beam Interface

XL-Override

End Detail

Main beam: Coupling
Cross Tee: Staked-on clip

Classification

Light duty LD

Profile







Exposed tee system

Colour Selection

White (WH)

PRELUDE XL32

24mm (15/16") Exposed Tee System

Prelude XL32						
	Item Number	Description	Dimensions			
			Rout Spacing	Length	Height	Width
	BP7342101C*	Main Beam: Flat Faced 24mm Tee (C3 Coupling Connection)	150mm	3000mm	32mm	24mm
	BP7347101C*		6"	120"	1-1/4"	15/16"
	BP313061	Cross Tee: Flat Faced 24mm Tee (XL Clip Connection – override with Main Beam)	600mm	1200mm	27mm	24mm
	XL7147WH		24"	48"	1-1/16"	15/16"
	BP312011	Cross Tee: Flat Faced 24mm Tee (XL Clip Connection – override with Main Beam)	–	600mm	25mm	24mm
	XL7124WH		–	24"	1"	15/16"
Wall Mounting						
	BPT1935H	3000mm Angle Molding	–	3000mm	19mm	19mm
<div> Sustainability</div>		<div> 25%</div>				

Note: Hanger Spacing 1200mm, *load: 8.12kg/m LD

Contact

For further details, please contact your local representative or email asia.support@knaufarmstrong.com